

Protection

Protection against electrical parts

Touching live parts with voltages of 50 V or more with bare hands or conductive tools, or touching ungrounded housings, can be dangerous and cause electric shock. Operating electrical equipment requires that certain parts unavoidably carry dangerous voltages.



High electrical voltage! Danger to life, severe bodily harm by electric shock!

- * Only those trained and qualified to work with or on electrical equipment are permitted to operate, maintain or repair this equipment.
- * Follow general construction and safety regulations when working on high voltage installations.
- * Before switching on power the ground wire must be permanently connected to all electrical units according to the connection diagram.
- * Do not operate electrical equipment at any time, even for brief measurements or tests, if the ground wire is not permanently connected to the points of the components provided for this purpose.
- * Before working with electrical parts with voltage higher than 50 V, the equipment must be disconnected from the mains voltage or power supply.
- * Make sure the equipment cannot be switched on again unintentionally.
- * The following should be observed with electrical drive and filter components:
 - * Wait five (5) minutes after switching off power to allow capacitors to discharge before beginning to work. Measure the voltage on the capacitors before beginning to work to make sure that the equipment is safe to touch.
 - * Never touch the electrical connection points of a component while power is turned on.
- * Install the covers and guards provided with the equipment properly before switching the equipment on. Prevent contact with live parts at any time.
- * A residual-current-operated protective device (RCD) must not be used on electric drives! Indirect contact must be prevented by other means, for example, by an overcurrent protective device.
- * Electrical components with exposed live parts and uncovered high voltage terminals must be installed in a protective housing, for example, in a control cabinet.

High electrical voltage on the housing! High leakage current! Danger to life, danger of injury by electric shock!

- * Connect the electrical equipment, the housings of all electrical units and motors permanently with the safety conductor at the ground points before power is switched on. Look at the connection diagram. This is necessary even for brief tests.
- * Connect the safety conductor of the electrical equipment always permanently and firmly to the supply mains. Leakage current exceeds 3.5 mA in normal operation.
- * Use a copper conductor with at least 10 mm² cross section over its entire course for this safety conductor connection!
- * Before startup, even for brief tests, always connect the protective conductor (ground wire). Otherwise, high voltages can occur on the housing and lead to electric shock.

Protection against dangerous movements

Dangerous movements can be caused by faulty control of the connected motors. Some common examples are:

Item
improper or wrong wiring of cable connections
incorrect operation of the equipment components
wrong input of parameters before operation
malfunction of sensors, encoders and monitoring devices
defective components
software or firmware errors

Dangerous movements can occur immediately after the equipment is switched on, or even after an unspecified period of trouble-free operation.

The monitoring in the drive components is normally sufficient to avoid faulty operation in the connected drives. Regarding personal safety, especially the danger of bodily injury and material damage, this alone cannot be relied upon to ensure complete safety. Until the integrated monitoring functions become effective, it must be assumed in any case that faulty drive movements will occur. The extent of faulty drive movements depends upon the type of control and the state of operation.



Dangerous movements! Danger to life, risk of injury, severe bodily harm or material damage!

Ensure personal safety by means of qualified and tested higher-level monitoring devices or measures



there is a possibility of loose parts flying off.

Mount the emergency stop switch in the immediate vicinity of the operator.

Verify that the emergency stop works before starting the machine. Don't operate the machine if the emergency stop is not working.

Isolate the drive power connection by means of an emergency stop circuit or use a starting lockout to prevent unintentional start.

Make sure that the drives are brought to a safe standstill before accessing or entering the danger zone. Safe standstill can be achieved by switching off the power supply contactor or by safe mechanical locking of moving parts.

Protection against contact with hot parts

Secure vertical axes against falling or dropping after switching off the motor power by, for example:



the vertical axes

Housings and surfaces could be extremely hot! Danger of injury! Danger of burns!

the vertical axes

motor brake or an external brake controlled directly by the drive controller

Do not touch hot surfaces near sources of heat! Danger of burns!

After the equipment has been switched off, wait at least ten (10) minutes to allow it to cool down before touching it.

Do not touch hot parts of the equipment, such as housings with integrated heat sinks and resistors. Danger of burns!

continued equipment use

Prevent the operation of high-frequency, remote control and radio equipment near electronics

Protection during handling and mounting
circuits and supply leads. If the use of such equipment cannot be avoided, verify the system and the installation for possible malfunctions in all possible positions of normal use before initial startup. If necessary, perform a special electromagnetic compatibility (EMC) test on the installation.

Under certain conditions, incorrect handling and mounting of parts and components may cause

Protection against magnetic / electromagnetic fields during operation and mounting



Risk of injury by incorrect handling! Bodily harm caused by crushing, shearing, cutting and mechanical shock!

Use appropriate mounting and transport equipment. Take precautions to avoid pinching and crushing. Use only appropriate tools. If specified by the product documentation, special tools must be used.

Use lifting devices and tools correctly and safely.

For safe protection wear appropriate protective clothing, e.g. safety glasses, safety shoes and safety gloves.

Never stand under suspended loads.

Clean up liquids from the floor immediately to prevent slipping.

From:

<https://dokuwiki.nilab.at/> - **NiLAB GmbH**
Knowledgebase

Permanent link:

<https://dokuwiki.nilab.at/doku.php?id=en:protection>

Last update: **2026/09/12 11:11**

