




ULCV 66



Mechanical Drawing



Load Rating



Fz [daN]	Cx [daN]	Cy [daN] (*)	Cox [daN]	Coy [daN] (*)	MoX [daNm]	MoY [daNm]	MoZ [daNm]
110	1904	1904↓ 1904↑	3091	3091↓ 3091↑	253	253	20,2

Technical data

Parameter	Symbol	Value	Unit
Max usable stroke		6500	mm
Total length	Ltot	C+Lc+340	mm

Carriage length	Lc	200	mm
Carriage usable length	Lu	200	mm
Extra-stroke (safety)	Ec	60	mm
Max speed		250	m/min
Max acceleration		100	m/s ²
Position repeatability		< 0.05	mm
Aluminium profile section		66 x 70	mm
Inertia momentum of aluminium profile	I _x	944288	mm ⁴
Inertia momentum of aluminium profile	I _y	993457	mm ⁴
Type of mechanic		linear guide with compact block	
Belt type		Poliuretan HTD-5M-17	
Pulley teeth number		30	
Diameter		47,75	mm
Linear movement per rotation		180	mm
Operating temperature		-20 / +60	degrees

From:

<https://dokuwiki.nilab.at/> - **NiLAB GmbH**
Knowledgebase

Permanent link:

<https://dokuwiki.nilab.at/doku.php?id=en:ulco:ulcv-66>

Last update: **2026/09/11 07:59**

