


Connectors Pinout

Connector type


Speedtec 2 x M23 (power) and M17 (signal encoder)

PIN	FUNCTION	CONNECTOR VIEW FRONT	PIN	FUNCTION
12	SIN		1	U
11	REFSIN		2	V
10	COS		Earth	PE
9	REFCOS		4	TSW or PTC+
8	-		5	TSW or PTC-
7	-		6	W
6	+7..12VDC			
5	GND			
4	DATA+			
3	DATA-			
2	-			
1	SHIELD			

Signal type



Oscilloscope acquisition of SIN and COS signals (REFCOS and REFSIN are 2.5V constant voltage).



Signal	Value
Peak value	0,9 V ... 1,1 V
Signaloffset REFSIN, REFCOS	2,2 V ... 2,8 V

PTC Thermal sensor

LMA actuator integrates Thermal switch (normally closed, open at maximum winding temperature) or PTC600 thermal sensor. This thermal sensor is composed by 3 x PTC series connected mounted in each primary part of the integrated linear motor. In order to map the PTC curve inside the drive please use DN44082 thermistor type curve, with 1800 Ohm of thermistor reset threshold and 3300 ohm of thermistor trip threshold.

From:

<https://dokuwiki.nilab.at/> - NiLAB GmbH Knowledgebase

Permanent link:

https://dokuwiki.nilab.at/doku.php?id=lma_actuator:connectors

Last update: **2024/05/20 07:08**

